

Haarby Løglægger HSK 97



Haarby Løglægger for lægning af stikløg.

Løglæggeren kan lægge løg op til 4 cm i diameter og kan i standard-gearing lægge 30 løg pr. meter (Ø 2,5 cm).

Udlægningsmængden kan øges ved ændring på gearkasse (20 gear). Løgekassen rummer 100 kg. løg pr. række, men som ekstraudstyr fås kasseforøger.

Maskinen kan påbygges gødningsanlæg (fast / flydende), som nedfælder startgødning til løgene. Såkassen er placeret så lavt, at det er muligt at se løgtilgangen til læggeskæret fra traktoren.

Rækkeafstand:

3 rækker min. 43 cm., max. 47 cm., sporvidde 150 cm

4 rækker min. 30 cm., max. 35 cm., sporvidde 150 cm

5 rækker min. 30 cm., max. 30 cm., sporvidde 180-200 cm

6 rækker min. 30 cm., max. 30 cm., sporvidde 210 cm

Fremkørselshastighed efter forholdene (ca. 4-6 km./t.)

Rækkesektionen er monteret med selvrensende gummitrykruller for / bag. Disse er højdejusterbare og bestemmer læggedybden.


Skæret er 10 cm. bredt og kan indstilles fra 2-6 cm i dybden.

Yderligere er der monteret en gummi mellemtrykrulle til at presse løgene ned i den fugtige jord. Rilledækkerne indstilles, så de dækker løgene ens.

Læggeskær og rilledækker er i rustfrit stål, som sikrer lang levetid samt hindrer jorden i at klæbe på delene. Landhjul er højdejusterbare, så stikløg kan sættes på kamme.

Ekstraudstyr:

- Gødningsanlæg.
- Nettrykrulle som erstatning for gummitrykrulle bag.
- Teleskop stenplov foran rækken til fjernelse af knolde, sten og tør jord.
- Løgekasseforøger giver større kapacitet.
- Mekaniske eller hydrauliske markører.
- Rulleskær tildækker.



Haarby Smedie & Kunstsmiede ApS

Telefon +45 64 73 21 50
Mobil +45 20 74 42 84
Fax +45 64 73 25 50

E-mail info@haarbysmedie.dk
Web www.haarbysmedie.dk

SPECIALMASKINER: Såning • Lægning • Plantning • Høstning • Jordtilberedning



Haarby Onion Set Planter HSK 97



Haarby Onion Set Planter.

The onion planter plants onions with a maximum diameter of 4 cm. It plants above 30 onions per meter (size 2,5 cm), increase by changing of gearbox (20 gear).

The onion planter contains 100 kg. onions per row, as extra equipment there is a box extension.

The machine can be fitted with fertilizer system (liquid / solid).

The sowing box is fixed so low that it is possible from the tractor to see the onions fall into the planting coulters.

Row widths:

3 rows min. 43 cm., max. 47 cm., wheel track 150 cm

4 rows min. 30 cm., max. 35 cm., wheel track 150 cm

5 rows min. 30 cm., max. 30 cm., wheel track 180-200 cm


6 rows min. 30 cm., max. 30 cm., wheel track 210 cm

Forward speed after the conditions (4-6 km./h.)

The row unit is fitted with selfcleaning zero pressure wheels front / rear. They are height adjustable and determine the plant depth. After the coulter, there is a press wheel to take care of the onions to be sure that it has contact with the moist soil. Armcovers can be adjusted, so it covers the onions correctly. Coulters and armcovers are made in stainless steel, it lasts longer and no moist soil will stick to it. Adjustable landwheel for planting on beds and flat land.

Extra equipment:

- Fertilizer systems.
- Cage rear wheel instead of zero rubber wheel.
- Telescopic clod deflector.
- Onion box extensioner.
- Manual or hydraulic markers.
- Disc covers



Haarby Smedie & Kunstsmiede ApS

Telefon +45 64 73 21 50
Mobil +45 20 74 42 84
Fax +45 64 73 25 50

E-mail info@haarbysmedie.dk
Web www.haarbysmedie.dk

SPECIALMASKINER: Såning • Lægning • Plantning • Høstning • Jordtilberedning

